


REV	DESCRIPTION	DESIGN	DATE
A0	Release	李润	2016.05.12
A1	①改前亮锡/改后雾锡	李润	2016.08.08



Board Layout
General Tolerance: ±0.05

主要技术参数 Main Specifications

- 额定电阻 (Contact resistance): $\leq 20m\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 1000M\Omega$
- 额定电压 (Rated voltage): 125 V AC DC
- 额定电流 (Rated current): 1.0A AC DC
- 耐电压 (Withstand Voltage): 1500V AC/minute
- 温度范围 (Temperature Range): $-40^{\circ}C \sim +110^{\circ}C$

ORDER INFORMATION:

L020A-02-B1MB-P-C

PART No.	SPECIAL CODE:
No. FOR CIRCUITS:	C=11.0*3.0
02	PACKAGING:
PLASTIC MATERIAL:	P=PE
B1M=PA46 (BEIGE)	PLATING:
	ⓅB=MATTE Sn

ITEM	COMPONENT	Q'TY	MATERIAL	FINISH
C				
B	CONTACT	2 PCS	Brass	Sn-plated
A	PEDESTAL	1 PCS	PA46	UL 94V-0, COLOR:BEIGE

X.±0.5		X.±5°	USE: CUSTOMER	TITLE: -	
.X±0.3	.X±2°	APPD: 邵敬和		3.6mmPITCH 180°WAFER DIP TYPE	
.XX±0.25	.XX±1°	CHKD: 田峰	PART NO.:		
--	--	DR: 吴丹平	L020A-02-B1MB-P-C		
UNITS: mm			DWG NO.:		
			JKUN/GCCP-0228		
			SCALE	SHEET	
			1 : 1	1 / 1	

JKUN 温州健坤接插件有限公司
WENZHOU JKUN CONNECTOR CO., LTD.